

THE  
**Honey<sup>M</sup>**  
 FRAMED 60 LAYOUT MODULE



**60 LAYOUT**  
 MONOCRYSTALLINE MODULE

**325-340W**  
 POWER OUTPUT RANGE

**19.9%**  
 MAXIMUM EFFICIENCY

**0~+5W**  
 POSITIVE POWER TOLERANCE

Product DD06M.08(II) | Color of BS White | Power Range 325 -340W

Founded in 1997, Trina Solar is the world's leading total solution provider for solar energy. With local presence around the globe, Trina Solar is able to provide exceptional service to each customer in each market and deliver our innovative, reliable products with the backing of Trina as a strong, bankable brand. Trina Solar now distributes its PV products to over 100 countries all over the world. We are committed to building strategic, mutually beneficial collaborations with installers, developers, distributors and other partners in driving smart energy together.

**Comprehensive Products and System Certificates**

IEC61215/IEC61730/IEC61701/IEC62716  
 ISO 9001: Quality Management System  
 ISO 14001: Environmental Management System  
 ISO14064: Greenhouse Gases Emissions Verification  
 OHSAS 18001: Occupation Health and Safety Management System



**High power mono per cell**

- Up to 340W front power and 19.9% module efficiency with half-cut and MBB (Multi Busbar) technology bringing more BOS savings
- Lower resistance of half-cut and good reflection effect of MBB ensure high power



**High reliability**

- Ensured PID resistance through cell process and module material control
- Resistant to salt, acid and ammonia
- Certified to 5400 Pa positive load and 2400 Pa negative load




**High energy generation**


- Excellent IAM and low light performance validated by 3rd party with cell process and module material optimization
- Lower temp coefficient (-0.36%) and NMOT bring more energy leading to lower LCOE
- Better anti-shading performance and lower operating temperature

**PERFORMANCE WARRANTY**


10 Year Product Warranty · 25 Year Power Warranty




### DIMENSIONS OF PV MODULE(mm)



### I-V CURVES OF PV MODULE(340W)



### P-V CURVES OF PV MODULE(340W)



### ELECTRICAL DATA (STC)

Parameter	325	330	335	340
Peak Power Watts- $P_{MAX}$ (Wp)*	325	330	335	340
Power Output Tolerance- $P_{MAX}$ (W)	0 ~ +5			
Maximum Power Voltage- $V_{MPP}$ (V)	33.6	33.8	34.0	34.2
Maximum Power Current- $I_{MPP}$ (A)	9.67	9.76	9.85	9.94
Open Circuit Voltage- $V_{OC}$ (V)	40.4	40.6	40.7	41.1
Short Circuit Current- $I_{SC}$ (A)	10.3	10.4	10.5	10.6
Module Efficiency $\eta_m$ (%)	19.1	19.4	19.7	19.9

STC: Irradiance 1000W/m<sup>2</sup>, Cell Temperature 25°C, Air Mass AM1.5.  
 \*Measuring tolerance:  $\pm$ 3%.

### ELECTRICAL DATA (NMOT)

Parameter	246	250	254	257
Maximum Power- $P_{MAX}$ (Wp)	246	250	254	257
Maximum Power Voltage- $V_{MPP}$ (V)	31.6	31.7	31.9	32.1
Maximum Power Current- $I_{MPP}$ (A)	7.79	7.86	7.94	8.01
Open Circuit Voltage- $V_{OC}$ (V)	38.1	38.3	38.4	38.7
Short Circuit Current- $I_{SC}$ (A)	8.30	8.38	8.46	8.54

NMOT: Irradiance at 800W/m<sup>2</sup>, Ambient Temperature 20°C, Wind Speed 1m/s.

### MECHANICAL DATA

Solar Cells	Monocrystalline
Cell Orientation	120 cells (6 $\times$ 20)
Module Dimensions	1698 $\times$ 1004 $\times$ 35 mm (66.85 $\times$ 39.53 $\times$ 1.38 inches)
Weight	18.7kg (41.2lb)
Glass	3.2mm (0.13 inches), High Transmission, AR Coated Heat Strengthened Glass
Encapsulant Material	EVA
Backsheet	White
Frame	35 mm (1.38 inches) Anodized Aluminium Alloy
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm <sup>2</sup> (0.006 inches <sup>2</sup> ), Portrait: N 140mm/P 285mm(5.51/11.22inches) Landscape: N 1200 mm /P 1200 mm (47.24/47.24 inches)
Connector	MC4 / TS4

### TEMPERATURE RATINGS

NMOT (Nominal Module Operating Temperature)	41 C ( $\pm$ 3 C)
Temperature Coefficient of $P_{MAX}$	- 0.36%/ C
Temperature Coefficient of $V_{OC}$	- 0.26%/ C
Temperature Coefficient of $I_{SC}$	0.04%/ C

(Do not connect Fuse in Combiner Box with two or more strings in parallel connection)

### MAXIMUM RATINGS

Operational Temperature	-40~+85 C
Maximum System Voltage	1000V DC (IEC) 1000V DC (UL)
Max Series Fuse Rating	20A

### WARRANTY

10 year Product Workmanship Warranty
25 year Power Warranty

(Please refer to product warranty for details)

### PACKAGING CONFIGURATION

Modules per box: 30 pieces
Modules per 40' container: 780 pieces